

LIFT WISE[®]

Self Propelled Tire Handlers



254-757-1177 | sales@lift-wise.com | lift-wise.com

SPECIFICATIONS

	SP3500	SP6000	SP8000
Load Capacity	3500 lb (1588 kg)	6000 lb (2722 kg)	8000 lb (3629 kg)
Minimum Tire Diameter	48" (1219 mm)	64" (1626 mm)	76" (1930 mm)
Maximum Tire Diameter	86" (2184 mm)	107" (2718 mm)	109" (2769 mm)
Maximum Tire Width	32" (813 mm)	42" (1067 mm)	46" (1168 mm)
Lift Height	14" (356 mm)	22" (559 mm)	24" (610 mm)
Side Shift	+/-3"	+/-3"	+/-3"
Weight	2102 lb (953 kg)	3175 lb (1440 kg)	3186 lb (1445 kg)
Tire Rotation	Continuous	Continuous	Continuous

OPTIONS

- Modified capacities and features to meet your applications
- Removable 3rd roller (SP6000) to accommodate smaller tires.
- Adjustable arms to secure tire
- Tire racks available

FEATURES

- Utilizes the maneuverability and familiar controls of a pallet truck.
- Operated by tethered controller
- Tire is secured using a cinching strap.
- Tires can be precisely positioned using the lift, side-shift, and rotation functions.
- Onboard battery charger
- Operation, maintenance and parts manual



CUSTOMIZED

MATERIAL HANDLING

SOLUTIONS

Material and specifications are subject to change without notice. Units in photos may include optional features. Contact a LiftWise representative for available options. LiftWise® and the LiftWise logo are registered trademarks of Fritel & Associates, LLC and may not be used without permission.

© 2023 Diversified Product Development All Rights Reserved.



254-757-1177 | sales@lift-wise.com | lift-wise.com