

LIFT WISE

Post Pullers



254-757-1177 | sales@lift-wise.com | lift-wise.com

Now you can remove and reuse most types of posts with your truck equipped with the Bemis Post Puller

ADDITIONAL INFORMATION

PPF 203 with 12V pump is not appropriate for over 25% duty cycle.

PPF 203 is available with or without power unit



ECONOMICAL and EFFICIENT

- **HARD TO REACH SPOTS EASILY REACHED**
Now you can reach over gullies, over guardrails, above or below grade level... and all those other hard to reach spots.
- **PULL MULTIPLE POSTS FROM ONE TRUCK POSITION**
The Pivot mount and extension cylinder allows you to pull more than one post without moving the truck.

Performance Criteria

	REGULAR DUTY PPF 203	HEAVY DUTY PPF 295
Truck Requirement:	Requires 3/4 ton or heavier truck	Requires a 17,500 lb. GVW vehicle with a hydraulic system of 2-3 GPM @ 2,500 PSI.
Boom Extension	30"	36"
Side Reach	91 1/2" (from pivot point)	119" (from pivot point)
Pulling Force	10,000 lbs.	30,000 lbs.
Material:		
Support Beam	4" x 4" x 3/16" sq. tube	6" x 4" x 3/16" rect. tube
Outer Boom	2 1/2" x 1 1/2" x 3/16" rect. tube	2 1/2" x 2 1/2" x 3/16" sq. tube
Inner Boom	1" x 2" bar	2" x 2" x 3/16" sq. tube
Frame Mounting Plates	9" x 6" x 3/8" plate	9" x 6" x 3/8" plate
Cylinders:		
Boom Lift Cylinder	2" bore x 1 1/8" rod x 6" stroke	2" bore x 1 1/8" rod x 6" stroke
Boom Extend Cylinder	2" bore x 1 1/8" rod x 30" stroke	2" bore x 1 1/8" rod x 36" stroke
Puller Cylinder	2 1/2" bore x 1 1/4" rod x 12" stroke	4" bore x 1 1/2" rod x 12" stroke
Shipping Weight	500 lb.	700 lb.



Material and specifications are subject to change without notice. Units in photos may include optional features. Contact a LiftWise representative for available options. LiftWise® and the LiftWise logo are registered trademarks of Fritel & Associates, LLC and may not be used without permission.
© 2026 Diversified Product Development All Rights Reserved.



254-757-1177 | sales@lift-wise.com | lift-wise.com